







## PACKAGE AIR CONDITIONERS

<p><b>3 - 5 TONS</b></p> <p><b>PAF3</b></p> <ul style="list-style-type: none"> <li>Energy Star<sup>®</sup></li> <li>13 SEER</li> <li>3 - 5 tons</li> <li>Scroll compressor</li> <li>R-22</li> <li>Slip-in electric heat 5 - 20 kw</li> <li>208/230 or 460 volts</li> </ul> 	<p><b>3 - 5 TONS</b></p> <p><b>PAF</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>10 SEER</li> <li>3 - 5 tons</li> <li>Scroll compressor on 5 ton</li> <li>Reciprocating compressor on 3 - 4 ton models</li> <li>R-22</li> <li>Slip-in electric heat 5 - 20 kw</li> <li>208/230 or 460 volts</li> </ul>	<p><b>2 - 5 TONS</b></p> <p><b>PAX4 (Single Phase)</b></p> <ul style="list-style-type: none"> <li>Energy Star<sup>®</sup></li> <li>14.5 SEER</li> <li>2 - 5 tons</li> <li>Scroll compressor</li> <li>2-stage cool</li> <li>R-410A</li> <li>GE ECM 2.3 variable-speed motor</li> <li>Slip-in electric heat 5 - 20 kw</li> <li>208/230 volts</li> </ul> <p><b>PAX4 Limited Warranty:</b></p> <ul style="list-style-type: none"> <li>Compressor - 10 Yrs.</li> <li>Coil - 7 Yrs.</li> <li>Parts - 5 Yrs.</li> <li>No Hassle*** - 7 Yrs.</li> </ul> 	<p><b>3 - 5 TONS</b></p> <p><b>PAX3</b></p> <ul style="list-style-type: none"> <li>Energy Star<sup>®</sup></li> <li>13 SEER</li> <li>3 - 5 tons</li> <li>2-stage scroll compressor</li> <li>R-410A</li> <li>Slip-in electric heat 5 - 20 kw</li> <li>208/230 or 460 volts</li> </ul>	<p><b>3 - 5 TONS</b></p> <p><b>PAB (Belt Drive)</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>10 SEER</li> <li>3 - 5 tons</li> <li>Scroll compressor</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>7.5 TONS</b></p> <p><b>PAF (Belt Drive)</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>9.0 SEER</li> <li>7.5 tons</li> <li>Scroll compressor</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>6 TONS</b></p> <p><b>PAE072</b></p> <ul style="list-style-type: none"> <li>Energy Star<sup>®</sup></li> <li>ASHRAE 90.1 efficiency</li> <li>10.3 EER</li> <li>6 tons</li> <li>Scroll compressor</li> <li>Single-stage cooling</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>6 TONS</b></p> <p><b>PAS072</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>Up to 9.0 EER</li> <li>6 tons</li> <li>Scroll compressor</li> <li>Single-stage cooling</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>7.5 - 12.5 TONS</b></p> <p><b>PAE090, PAE102, PAE120, PAE150</b></p> <ul style="list-style-type: none"> <li>ASHRAE 90.1 efficiency</li> <li>Up to 10.3 EER</li> <li>7.5 - 12.5 tons</li> <li>Scroll compressors on 8.5 - 12 ton models</li> <li>2-stage cooling</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>7.5 - 12.5 TONS</b></p> <p><b>PAS090, PAS120, PAS150</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>Up to 8.9 EER</li> <li>7.5 - 12.5 tons</li> <li>Scroll compressors on 12.5 ton models</li> <li>2-stage cooling</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>15, 17.5, 20 TONS</b></p> <p><b>PAE180, PAE210, PAE240</b></p> <ul style="list-style-type: none"> <li>ASHRAE 90.1 efficiency</li> <li>Up to 10.0 EER</li> <li>15, 17.5, 20 tons</li> <li>Scroll compressors</li> <li>2-stage cooling</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>15, 17.5, 20 TONS</b></p> <p><b>PAS180, PAS210, PAS240</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>Up to 8.8 EER</li> <li>15, 17.5, 20 tons</li> <li>Scroll compressors</li> <li>2-stage cooling</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>25 TONS</b></p> <p><b>PAS300</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>Up to 8.7 EER</li> <li>25 tons</li> <li>Scroll compressors</li> <li>2-stage cooling</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>25 TONS</b></p> <p><b>PAE300</b></p> <ul style="list-style-type: none"> <li>ASHRAE 90.1 efficiency</li> <li>Up to 9.8 EER</li> <li>25 tons</li> <li>Scroll compressors</li> <li>2-stage cooling</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>
--	--	---	--	--	---	---	--	---	---	--	--	--	---

## PACKAGE GAS/ELECTRICS

<p><b>3 - 5 TONS</b></p> <p><b>PGF3</b></p> <ul style="list-style-type: none"> <li>Energy Star<sup>®</sup></li> <li>13 SEER</li> <li>3 - 5 tons</li> <li>Up to 80% AFUE</li> <li>Aluminized serpentine clamshell heat exchanger</li> <li>Scroll compressor</li> <li>R-22</li> <li>208/230 or 460 volts</li> </ul> 	<p><b>3 - 5 TONS</b></p> <p><b>PGF/PGC</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>10 SEER</li> <li>3 - 5 tons</li> <li>Up to 80% AFUE</li> <li>Aluminized serpentine clamshell heat exchanger</li> <li>High-efficiency compressors (scroll on 5 ton)</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>2 - 5 TONS</b></p> <p><b>PDX4 (Single Phase)</b></p> <ul style="list-style-type: none"> <li>Energy Star<sup>®</sup></li> <li>14.5 SEER, 78% AFUE</li> <li>Up to 8.0 HSPF</li> <li>R-410A</li> <li>GE ECM 2.3 variable-speed motor</li> <li>Dual fuel - gas/electric &amp; heat pump</li> <li>2-stage cool</li> <li>2-stage heat</li> <li>2-stage inducer motor assembly</li> <li>2-stage gas valve</li> <li>Stainless steel heat exchanger</li> <li>Scroll compressor</li> <li>Advanced furnace control board</li> <li>New dual fuel thermostat</li> <li>208/230 volts</li> </ul> <p><b>PDX4/PGX4 Limited Warranty:</b></p> <ul style="list-style-type: none"> <li>Heat exchanger - Lifetime-limited</li> <li>Compressor - 10 Yrs.</li> <li>Coil - 10 Yrs. (PDX4), 7 Yrs. (PGX4)</li> <li>Parts - 7 Yrs. (PDX4), 5 Yrs. (PGX4)</li> <li>No Hassle*** - 10 Yrs. (PDX4), 7 Yrs. (PGX4)</li> </ul> 	<p><b>2 - 5 TONS</b></p> <p><b>PGX4 (Single Phase)</b></p> <ul style="list-style-type: none"> <li>Energy Star<sup>®</sup></li> <li>14.5 SEER, 78% AFUE</li> <li>R-410A</li> <li>GE ECM 2.3 variable-speed motor</li> <li>2-stage cool</li> <li>2-stage heat</li> <li>2-stage inducer motor assembly</li> <li>2-stage gas valve</li> <li>Stainless steel heat exchanger</li> <li>Scroll compressor</li> <li>Advanced furnace control board</li> <li>208/230 volts</li> </ul>	<p><b>3 - 5 TONS</b></p> <p><b>PGX3</b></p> <ul style="list-style-type: none"> <li>Energy Star<sup>®</sup></li> <li>13 SEER</li> <li>3 - 5 tons</li> <li>Up to 79.6% AFUE</li> <li>Stainless steel tubular heat exchanger</li> <li>2-stage scroll compressor</li> <li>R-410A</li> <li>208/230 or 460 volts</li> </ul>	<p><b>3 - 5 TONS</b></p> <p><b>PGB (Belt Drive)</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>10 SEER</li> <li>3 - 5 tons</li> <li>80% AFUE</li> <li>Tubular heat exchanger with aluminized coating</li> <li>Scroll compressor</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>7.5 TONS</b></p> <p><b>PGF (Belt Drive)</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>9.0 EER</li> <li>7.5 tons</li> <li>81% AFUE</li> <li>Tubular heat exchanger with aluminized coating</li> <li>Scroll compressor</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>6 TONS</b></p> <p><b>PGE072</b></p> <ul style="list-style-type: none"> <li>ASHRAE 90.1 efficiency</li> <li>10.1 EER</li> <li>6 tons</li> <li>80% AFUE</li> <li>Tubular heat exchangers</li> <li>2-stage gas heat</li> <li>Single-stage cooling</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>6 TONS</b></p> <p><b>PGS072</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>9.0 EER</li> <li>6 tons</li> <li>80% AFUE</li> <li>Tubular heat exchangers</li> <li>2-stage gas heat</li> <li>Single-stage cooling</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>7.5 - 12.5 TONS</b></p> <p><b>PGE090, PGE102, PGE120, PGE150</b></p> <ul style="list-style-type: none"> <li>ASHRAE 90.1 efficiency</li> <li>Up to 10.1 EER</li> <li>7.5 - 12.5 tons</li> <li>80% AFUE</li> <li>Tubular heat exchangers</li> <li>2-stage gas heat</li> <li>Scroll compressors on 8.5 - 12.5 ton models</li> <li>2-stage cooling</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>7.5 - 12.5 TONS</b></p> <p><b>PGS090, PGS120, PGS150</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>Up to 8.2 EER</li> <li>7.5 - 12.5 tons</li> <li>80% AFUE</li> <li>Tubular heat exchangers</li> <li>2-stage gas heat</li> <li>Scroll compressors on 12.5 ton models</li> <li>2-stage cooling</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>15, 17.5, 20 TONS</b></p> <p><b>PGE180, PGE210, PGE240</b></p> <ul style="list-style-type: none"> <li>ASHRAE 90.1 efficiency</li> <li>Up to 9.7 EER</li> <li>15, 17.5, 20 tons</li> <li>81% AFUE</li> <li>Tubular heat exchanger</li> <li>Scroll compressor on each circuit</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>15, 17.5, 20 TONS</b></p> <p><b>PGS180, PGS210, PGS240</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>Up to 8.7 EER</li> <li>15, 17.5, 20 tons</li> <li>81% AFUE</li> <li>Tubular heat exchanger</li> <li>Scroll compressor on each circuit</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>25 TONS</b></p> <p><b>PGS300</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>Up to 8.6 EER</li> <li>25 tons</li> <li>81% AFUE</li> <li>Tubular heat exchanger</li> <li>Scroll compressor on each circuit</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>25 TONS</b></p> <p><b>PGE300</b></p> <ul style="list-style-type: none"> <li>ASHRAE 90.1 efficiency</li> <li>Up to 9.7 EER</li> <li>25 tons</li> <li>81% AFUE</li> <li>Tubular heat exchanger</li> <li>Scroll compressor on each circuit</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>
---	---	---	---	---	--	--	--	--	--	--	---	--	--	---

## PACKAGE HEAT PUMPS

<p><b>3 - 4 TONS</b></p> <p><b>PHF3</b></p> <ul style="list-style-type: none"> <li>Energy Star<sup>®</sup></li> <li>13 SEER</li> <li>7.7 HSPF</li> <li>3 - 4 tons</li> <li>Scroll compressor</li> <li>R-22</li> <li>5 - 20 kw electric heat</li> <li>208/230 or 460 volts</li> </ul> 	<p><b>3 - 5 TONS</b></p> <p><b>PHF</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>10 SEER</li> <li>6.8 HSPF</li> <li>3 - 5 tons</li> <li>Scroll compressor</li> <li>R-22</li> <li>5 - 20 kw electric heat</li> <li>208/230 or 460 volts</li> </ul>	<p><b>2 - 5 TONS</b></p> <p><b>PHX4 (Single Phase)</b></p> <ul style="list-style-type: none"> <li>Energy Star<sup>®</sup></li> <li>14.5 SEER</li> <li>Up to 8.0 HSPF</li> <li>R-410A</li> <li>GE ECM 2.3 variable-speed motor</li> <li>2-stage cool</li> <li>3-stage heat</li> <li>Scroll compressor</li> <li>2 - 5 tons</li> <li>208/230 volts</li> </ul> <p><b>PHX4 Limited Warranty:</b></p> <ul style="list-style-type: none"> <li>Compressor - 10 Yrs.</li> <li>Coil - 7 Yrs.</li> <li>Parts - 5 Yrs.</li> <li>No Hassle*** - 7 Yrs.</li> </ul> 	<p><b>3 - 5 TONS</b></p> <p><b>PHX3</b></p> <ul style="list-style-type: none"> <li>Energy Star<sup>®</sup></li> <li>13 SEER</li> <li>7.7 HSPF</li> <li>3 - 5 tons</li> <li>2-stage scroll compressor</li> <li>R-410A</li> <li>208/230 or 460 volts</li> </ul>	<p><b>6 TONS</b></p> <p><b>PHE072</b></p> <ul style="list-style-type: none"> <li>Energy Star<sup>®</sup></li> <li>ASHRAE 90.1 efficiency</li> <li>10.5 EER</li> <li>6 tons</li> <li>Scroll compressors</li> <li>Single-stage cooling</li> <li>R-22</li> <li>208/230 or 460 volts</li> </ul> 	<p><b>6 TONS</b></p> <p><b>PHS072</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>9.05 EER</li> <li>6 tons</li> <li>Single-stage cooling</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>7.5 - 10 TONS</b></p> <p><b>PHE090, PHE102, PHE120</b></p> <ul style="list-style-type: none"> <li>Energy Star<sup>®</sup></li> <li>ASHRAE 90.1 efficiency</li> <li>Up to 10.3 EER</li> <li>7.5 - 10 tons</li> <li>Scroll compressors</li> <li>2-stage cooling</li> <li>R-22</li> <li>208/230 or 460 volts</li> </ul> 	<p><b>7.5 - 10 TONS</b></p> <p><b>PHS090, PHS120</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>Up to 8.9 EER</li> <li>7.5 - 10 tons</li> <li>Scroll compressors on 10 ton model</li> <li>2-stage cooling</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>13 - 15 TONS</b></p> <p><b>PHE156, PHE180</b></p> <ul style="list-style-type: none"> <li>ASHRAE 90.1 efficiency</li> <li>Up to 9.8 EER</li> <li>13 - 15 tons</li> <li>Single semi-hermetic compressor on 13 ton models</li> <li>Dual semi-hermetic compressors with independent refrigerant circuits on 15 ton models</li> <li>2-stage cooling</li> <li>R-22</li> <li>208/230 or 460 volts</li> </ul>	<p><b>6 - 20 TONS</b></p> <p><b>BAC / BHC</b></p> <ul style="list-style-type: none"> <li>6 - 20 tons</li> <li>TXV standard</li> <li>BHC units include check valves for heat pump applications</li> <li>High static design</li> <li>Multiposition</li> <li>5 - 50 kw electric heat</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>3 - 5 TONS</b></p> <p><b>BHV</b></p> <ul style="list-style-type: none"> <li>Belt drive</li> <li>3 - 5 tons</li> <li>Vertical direct expansion blower coil</li> <li>Copper tube/aluminum fin</li> <li>TXV standard</li> <li>Heat pump compatible</li> <li>5 - 20 kw electric heat</li> <li>208/230 or 460 volts</li> </ul>	<p><b>7.5 - 10 TONS</b></p> <p><b>EHV / EHH (Cased Coils)</b></p> <ul style="list-style-type: none"> <li>7.5 - 10 tons</li> <li>EHV - Vertical direct expansion coils</li> <li>EHH - Horizontal direct expansion coils</li> <li>Dual circuit (field-convertible to single circuit)</li> <li>Copper tube/aluminum fin</li> <li>TXV standard</li> <li>Heat pump compatible</li> </ul> <p>Coil only is shown, all models are cased coils</p>
--	---	--	---	---	--	--	--	---	---	---	---

## COMMERCIAL AIR HANDLERS

## SPLIT CONDENSING UNITS

<p><b>3 - 5 TONS</b></p> <p><b>H2A3, H4A3</b></p> <ul style="list-style-type: none"> <li>Energy Star<sup>®</sup></li> <li>13 SEER</li> <li>3 - 5 tons</li> <li>Scroll compressor</li> <li>2-speed fan motor</li> <li>20°F low ambient control</li> <li>Comfort Alert™ diagnostics**</li> <li>R-22 on H2A3 model</li> <li>R-410A on H4A3 model</li> <li>208/230 or 460 volts</li> </ul> 	<p><b>3 - 5 TONS</b></p> <p><b>N2A3</b></p> <ul style="list-style-type: none"> <li>Energy Star<sup>®</sup></li> <li>13 SEER</li> <li>3 - 5 tons</li> <li>Scroll compressor</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul> 	<p><b>3 - 5 TONS</b></p> <p><b>N2A0</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>10 SEER</li> <li>3 - 5 tons</li> <li>Scroll compressor on 4 &amp; 5 ton models</li> <li>R-22</li> <li>208/230 or 460 volts</li> </ul>	<p><b>6.3 TONS</b></p> <p><b>CAE075</b></p> <ul style="list-style-type: none"> <li>ASHRAE 90.1 efficiency</li> <li>10.3 EER</li> <li>6.3 tons</li> <li>Scroll compressor</li> <li>R-22</li> <li>0°F low ambient control</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>7.5 TONS</b></p> <p><b>CAE090</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>9.9 EER</li> <li>7.5 tons</li> <li>Tandem scroll compressors</li> <li>2-stage cooling</li> <li>R-22</li> <li>0°F low ambient control</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>10 TONS</b></p> <p><b>CAC120</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>9.1 EER</li> <li>10 tons</li> <li>2-stage scroll compressors</li> <li>2-stage cooling, one independent circuit</li> <li>R-22</li> <li>0°F low ambient control</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>7.5 TONS</b></p> <p><b>CAE091</b></p> <ul style="list-style-type: none"> <li>ASHRAE 90.1 efficiency</li> <li>10.6 EER</li> <li>7.5 tons</li> <li>Single circuit scroll compressors</li> <li>2-stage cooling</li> <li>R-22</li> <li>-20°F low ambient control</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>10 TONS</b></p> <p><b>CAE120</b></p> <ul style="list-style-type: none"> <li>ASHRAE 90.1 efficiency</li> <li>Up to 10.3 EER</li> <li>10 tons</li> <li>Single circuit scroll compressors</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>12.5 - 20 TONS</b></p> <p><b>CAE150, CAE180, CAE240</b></p> <ul style="list-style-type: none"> <li>ASHRAE 90.1 efficiency</li> <li>Up to 10.6 EER</li> <li>12.5 - 20 tons</li> <li>Single circuit tandem scroll compressors</li> <li>2-stage cooling</li> <li>R-22</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>3 - 5 TONS</b></p> <p><b>H2H3, H4H3</b></p> <ul style="list-style-type: none"> <li>Energy Star<sup>®</sup></li> <li>13 SEER</li> <li>3 - 5 tons</li> <li>Scroll compressor</li> <li>2-speed fan motor</li> <li>20°F low ambient control</li> <li>Comfort Alert™ diagnostics**</li> <li>R-22 on H2H3</li> <li>R-410A on H4H3</li> <li>208/230 or 460 volts</li> </ul> 	<p><b>3 - 5 TONS</b></p> <p><b>N2H3</b></p> <ul style="list-style-type: none"> <li>Energy Star<sup>®</sup></li> <li>13 SEER</li> <li>3 - 5 tons</li> <li>Scroll compressor</li> <li>R-22</li> <li>208/230 or 460 volts</li> </ul> 	<p><b>3 - 5 TONS</b></p> <p><b>N2H0</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>10 SEER</li> <li>3 - 5 tons</li> <li>Scroll compressor on most models</li> <li>R-22</li> <li>208/230 or 460 volts</li> </ul>	<p><b>6.3 TONS</b></p> <p><b>CHE075</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>10.0 EER</li> <li>6.3 tons</li> <li>Scroll compressor</li> <li>R-22</li> <li>0°F low ambient control</li> <li>208/230, 460 or 575 volts</li> </ul>	<p><b>7.5 TONS</b></p> <p><b>CHE090</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>10.1 EER</li> <li>7.5 tons</li> <li>Scroll compressor</li> <li>R-22</li> <li>0°F low ambient control</li> <li>208/230 or 460 volts</li> </ul>	<p><b>7.5 TONS</b></p> <p><b>CHE091</b></p> <ul style="list-style-type: none"> <li>Energy Star<sup>®</sup></li> <li>ASHRAE 90.1 efficiency</li> <li>10.4 EER</li> <li>7.5 tons</li> <li>Single circuit scroll compressor</li> <li>2-stage cooling</li> <li>R-22</li> <li>-20°F low ambient control</li> <li>208/230 or 460 volts</li> </ul> 	<p><b>10 TONS</b></p> <p><b>CHE120</b></p> <ul style="list-style-type: none"> <li>Energy Star<sup>®</sup></li> <li>ASHRAE 90.1 efficiency</li> <li>10.1 EER</li> <li>10 tons</li> <li>Single circuit scroll compressor</li> <li>R-22</li> <li>208/230 or 460 volts</li> </ul>	<p><b>15 TONS</b></p> <p><b>CHS180</b></p> <ul style="list-style-type: none"> <li>Standard efficiency</li> <li>9.0 EER</li> <li>15 ton</li> <li>Direct drive</li> <li>R-22</li> <li>Reciprocating, semi-hermetic compressor with spring isolators</li> <li>208/230 or 460 volts</li> </ul>
--	--	---	---	--	--	--	--	--	--	---	--	--	---	---	---	--

\* Most PDX4, PGX4, PAX4 and PHX4 models meet Energy Star<sup>®</sup> criteria.

\*\* Ask your distributor for details or visit [www.energystar.gov](http://www.energystar.gov).

\*\*\* Comfort Alert™ is a trademark of Capeland Corporation.

\*\*\*\* The No Hassle Replacement™ limited warranty applies to covered mainline models installed on or after January 1, 2006. A new equivalent replacement unit will be provided should the compressor, covered coil or heat exchanger fail during the No-Hassle period. Written authorization from your Tempstar distributor is required prior to replacing any unit. This warranty is a supplement to the standard product limited warranty. See [www.tempstar.com](http://www.tempstar.com) for the most current and complete warranty certificate and further details.

A full line of commercial accessories is available, including roof curbs (8", 14" and 24"), thru-the-base power kits, coil and hail guards, economizers (downflow and horizontal, fully-modulating and three-position), electric heaters, single point wiring kits for electric heaters, low ambient kits, power exhaust, gas conversion kits, and fresh air dampers (manual and motorized).

© 2007 International Comfort Products, LLC

Illustrations and photographs are only representative. Some product models may vary. As part of its commitment to quality, International Comfort Products reserves the right to change specifications on its products without notice.

Standard efficiency products are not approved for sale in California.

Tempstar Products are covered by the following parts-only limited warranties:

- Heat exchanger - 10 Yrs.
- Compressor - 5 Yrs.
- Parts - 1 Yr.